

## ILG3- Narrow Island Application:



CASE DATA	06	08	12
Anti-Sweat Amps	N/A	2.82	4.25
Fan Amps	N/A	1.26	1.26
Drain Heater Amps.	0.06	0.39	0.83
Light Amps	N/A	N/A	N/A
Defrost Load Amps (If elec-230V)	N/A	9.37	14.06
# Defrosts Required	N/A	1	1
BTU Requirements at -20°	N/A	4320	6480
BTU Requirements at -30°	N/A	4480	6720

**NOTE:** For sizing conventional/individual condensing units ADD 8% to BTU LOAD.

	<u>Defrost</u>	<u>Per Day</u>	<u>Fail Safe</u>	<u>Termination</u>
	Electric	1	60	55°F
		Frozen Food	Low Temp	Med. Temp
Discharge Air Velocity		120-130 FPM	120-130 FPM	120-130 FPM
Discharge Air Temp		-6°F	-14°F	+28°F

Type I refrigerator, intended for use in an area where the environmental conditions are controlled and maintained such that conditions do not exceed 75 deg F and 55% relative humidity. Kysor/Warren, whose policy is one of continuous improvement, reserves the right to change at any time, specifications, design or prices without incurring obligation. Dual-Jet and Air Defrost are registered trademarks of Kysor/Warren.

The above case model, has case lengths that are NSF approved.



Issue: Sept - 2006

